

# NOVALACK S U2

HIGH CONCENTRATED METALCOMPLEX DYES IN LIQUID FORM

- Good light fastness and high transparency
- Good dilution in water, polar solvents and ketones

- Easy application
- For wood coating

Diluted colour 1:10

Diluted colour 1:50



NOVALACK S - U2 • **LEMON YELLOW G**

Diluted colour 1:10

Diluted colour 1:50




NOVALACK S - U2 • **YELLOW 2R**




NOVALACK S - U2 • **ORANGE R**





NOVALACK S - U2 • **RED G**




NOVALACK S - U2 • **BORDEAUX B**



NOVALACK S - U2 • **BROWN 4R**



NOVALACK S - U2 • **BLUE B**



NOVALACK S - U2 • **BLACK R**

## DESCRIPTION

NOVALACK S - U2 products are high concentrated metal complex dyes in liquid form, for wood coating. NOVALACK S - U2 are suitable both for water and solvent based systems.

# NOVALACK S U2

HIGH CONCENTRATED METALCOMPLEX DYES IN LIQUID FORM



## MAIN FEATURES AND TECHNICAL INFO FOR USE

NOVALACK S - U2 products must be kept closed in a cool, dry place for storage.

In case of crystallization due to frosty condition, heat the product up to complete solubilisation.

The shelf life is 9 months, if properly stored.

## TECHNICAL DATA

	NOVALACK S - U2
Physical appearance	LIQUID
Colour strength %	100 ± 5
pH	5 - 10
Solid content %	10 - 40

The technical data above stated are presented in good faith and to the best of our knowledge. They should serve only as approximate guidance and therefore customers are kindly advised to test and ascertain the performance of our products in the operating conditions existing at their end, to satisfy themselves about their suitability in a given industrial application.